

CAPACITY

Front load tray - 200lb (90 kg) Front load deck - 250lb (113 kg) Operator's compartment - 300lb (136 kg)



Designed for on level surfaces.





OPERATOR CONTROLS

The right-hand opertor control pod features fingertip lift/lower buttons for the operator platform, front load tray, horn, and travel.



LEFT HAND

RIGHT HAND

PMDC Drive Motor

Permanent magnet DC driver motor delivers run times of up to 4 hours of continuous operation on a single charge through a Zapi 24v infinity variable travel controller. Travel speeds are automatically reduced when elevated or tightly turning.

DC Lift Motor

Can lift the operator to a maximum elevation of 118".

Elevating System

I-beam mast design with dual lifting chains ensures solid stability characteristics at height.

Powered Front Load Tray

The lifting cylinder used to elevate the tray is shielded with an angled cover to protect it and items on the lower load deck from damage. The front load deck features a single piece rubber powerhead cover that may be removed to access the unit's mechanical, battery and charger systems for maintenance.

Hydraulic Pump & Reservoir

The hydraulic pump & reservoir is fully enclosed within the powerhead to reduce chances for leakage when used in a commercial enviroment and lowering valve is located on the chassis should the unit ever become stuck in the air.


Chassis

An all steel chassis provides good stability support at height while loaded, and exceptional durability to extend the equipment's service life.

Operator's Compartment

The compartment floor, rear gates and mast cap are cushioned for operator comfort. Obstruction presence sensors are included below the operator's compartment on the lower chassis.


OVERVIEW +FEATURES





Front load tray

29" x 21"(Lowers 19" from max) Front load deck 29" x 21"(Chassis, does not elevate) Battery & charger (2) 12v 120AH AGM batteries Integral 110 VAC plug-in smart charger Wheels & tires Drive tires: 8.3" X 2.8" polyurethane Rear tires: 9.8" x 3.9" non-marking rubber Electro mechanical brake is located on the front drive wheel.



Standard Options

- Powered front load tray
- Electronic power steering
- Forward facing blue light
- Rear flashing warning light
- Battery discharge indicator w/hour meter
- Accessory bars and file pouch
- · Cushioned floor mat and mast cap
- Integral 24v battery and 110v charger
- Key switch, horn, emergency power disconnect, slope alarm, stability tabs

Optional

- Audible back-up or travel alarm
- Plexiglass insert for front load tray
- Rail guidance

Corporate 410 Admiral Blvd Mississauga, ON, Canada L5T 2N6 905.457.3900 f 905.457.2313 **USA** 6350 Burnt Poplar Road Greensboro, NC 27409 www.bluegiant.com

Blue Giant offers a full line of dock levelers, dock safety equipment, seals and shelters, accessories, ergonomic and scissor lift equipment and industrial trucks. Concurrent with our continuing product improvement program, specifications are subject to change without notice. Please contact Blue Giant for latest information. Some features illustrated may be optional in certain market areas.

AUTHORIZED DEALER

If calling within North America: t 1.800.872.2583 f 1.888.378.5781

IT-BG0-311019 © Copyright Blue Giant Equipment Corporation 2019